

ID ECCO Smart 2D-TR

NFC programmer with QR code reader for current programming

Product description

- ID ECCO Smart 2D-TR is a mobile Barcode & RFID detection device with performant scan engine and powerful NFC interface
- For efficient programing of Tridonic LED drivers either by reading a special QR code or use the device in combination with the 4service NFC mobile App
- Further Information see www.tridonic.com/ES2D
- 1 year guarantee (conditions at www.tridonic.com)





ID ECCO Smart 2D-TR
NFC programmer with QR code reader for current programming

Technical data

| | |
|--|---|
| Housing material body | Double-walled Inside: robust ABS, Outside: protective rubber coating |
| Ambient temperature ta | -20 ... +55 °C |
| Storage temperature ts | -20 ... +60 °C |
| Guarantee (conditions at www.tridonic.com) | 1 year |
| Type of protection | IP64 |
| Dimensions LxWxH | 87 x 48 x 26 mm |

Ordering data

| Type | Article number | Packaging, carton | Weight per pc. |
|--------------------------|----------------|-------------------|----------------|
| Feig ID ECCO Smart 2D-TR | 28004649 | 50 pc(s). | 0.098 kg |

1. Common

ID ECCO Smart 2D-TR is a mobile Barcode & RFID detection device with performant scan engine and powerful NFC interface for efficient programming of Tridonic LED drivers either by reading a special QR code or use the device in combination with the 4serviceAPP NFC mobile App.

Hardware compatibility:

The driver must have an NFC interface. Only current can be set. The ECCO Smart hardware is a product of FEIG ELECTRONIC in Germany. Therefore, the Tridonic version we distributed differs only in the installed firmware. This firmware is written exclusively for us.

An ECCO Smart purchased directly from Feig or another source does not have the same range of functions and cannot be used with Tridonic NFC drivers.

Following drivers are not supported:

28003875, 28003876, 28003877, 28003878, 28003879, 28003880, 28004330.

Manual:

The user manual and information about the QR codes can be found here: www.tridonic.com/ES2D

2. Additional technical data

| | |
|-----------------------------------|---|
| Battery | 1,300 mAh Lithium Polymer, 3.7 V |
| Operation time | up to 16 hours |
| Loading time battery | approx. 3 – 4 hours |
| Loading note | charging via USB mini port, cable included |
| Temperature range loading battery | 0 ... +55 °C |
| Operating frequency | 13.56 MHz |
| Antenna | integrated |
| RF transmitting power | 1.5 W HF Reader IC |
| Supported Barcodes 2D | DataMatrix, QR Code |
| Protocol | Zhaga Book 25 |
| Indicator | LED (red, green, yellow, blue) Speaker Vibration feedback |
| Keyboard | 4 keys |
| Interfaces | USB, Bluetooth LE |
| Drop | 1.6 m drop to concrete |

3. Miscellaneous

3.1 Disposal of equipment



Return old devices in accordance with the WEEE directive to suitable recycling facilities.

3.2 Conditions of use and storage

Environmental conditions: 5 % up to max. 95 %, not condensed

Storage temperature: -20 °C up to max. +60 °C

The devices have to be acclimatised to the specified temperature range (ta) before they can be operated.

3.3 Additional information

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Zumtobel Group AG is under license.

Tridonic GmbH & Co. KG is a subsidiary of Zumtobel Group AG.

Additional technical information at www.tridonic.com → Technical Data

Lifetime declarations are informative and represent no warranty claim. No warranty if device was opened.