



Module ELA TW ADV2

Modules ELA advanced

Product description

- Tunable White LED module with 2,700 and 6,500 K SMT packages
- Edgelit panel for direct recessed mount and surface or suspended mount with accessories
- With pre-installed connection cable and integrated plug
- For suspended ceiling grid measure of 600 mm
- IK rating IK02
- Product colour (frame) RAL 9003
- Diffusor material standard article: PS, diffusor material TPA article (fulfills the TPA requirements): PS
- Lightguide material: PMMA
- Long lifetime: 50,000 hours
- 5 years guarantee (conditions at www.tridonic.com)

Optical properties

- Useful luminous flux 3,850 lm at Irated and tp = 25 °C
- Efficacy of the LED module 123 lm/W at Irated and tp = 25 °C
- High colour rendering index CRI > 80
- Small colour tolerance MacAdam 4[®]
- Small luminous flux tolerances
- UGR < 19

Mechanical properties

- Module dimension 595 x 595 mm

System solution

- Combine Tridonic`s LED modules and dimmable drivers to achieve an outstanding system efficacy (configuration possible via <https://setbuilder.tridonic.com/>)



Standards, page 6

Colour temperatures and tolerances, page 10






Module ELA TW ADV2

Modules ELA advanced

Technical data

Beam characteristic	90°
Ambient temperature range	-20 ... +40 °C
tp rated	45 °C
tc	70 °C
Irated	900 mA
Imax	1,050 mA
Max. permissible LF current ripple	1,365 mA
Max. permissible peak current	1,500 mA / max. 10 ms
Max. working voltage for insulation SELV	< 60 V
Insulation test voltage	0.5 kV
ESD classification	severity level 2
Risk group (IEC 62471) [®]	RG0
Classification acc. to IEC 62031	Independent
Type of protection	IP20
Lumen maintenance L70B50	50,000 h
Guarantee	5 years



Ordering data

Type	Article number	Colour temperature	Packaging carton [®]	Weight per pc.
ELA 600x600mm 3800lm 827-865 ADV2	28003282	2,700 – 6,500 K	5 pc(s).	2.50 kg
ELA 600x600mm 3800lm 827-865 ADV2 TPA	28004047	2,700 – 6,500 K	5 pc(s).	2.65 kg

[®] Orders only in full carton quantities.

Specific technical data

Type [®]	Colour temperature	Photo-metric code	Useful luminous flux at tp = 25 °C [®]	Expected luminous flux at tp rated [®]	Typ. forward current	Min. forward voltage at tp rated	Max. forward voltage at tp = 25 °C	Power consumption Pon at tp = 25 °C [®]	Efficacy of the module at tp = 25 °C	Expected efficacy of the module at tp rated	Colour rendering index CRI
Operating mode HE at 700 mA											
ELA 600x600mm 3800lm 827-865 ADV2	2,700 K	827/469	–	2,850 lm	700 mA	321 V	35.9 V	–	–	120 lm/W	> 80
	3,000 K	830/469	–	2,985 lm	700 mA	321 V	35.9 V	–	–	126 lm/W	> 80
	4,000 K	840/469	–	3,165 lm	700 mA	30.5 V	34.1 V	–	–	141 lm/W	> 80
	6,500 K	865/469	–	3,165 lm	700 mA	32.1 V	35.9 V	–	–	134 lm/W	> 80
ELA 600x600mm 3800lm 827-865 ADV2 TPA	2,700 K	827/469	–	2,850 lm	700 mA	32.1 V	35.9 V	–	–	120 lm/W	> 80
	3,000 K	830/469	–	2,985 lm	700 mA	32.1 V	35.9 V	–	–	126 lm/W	> 80
	4,000 K	840/469	–	3,165 lm	700 mA	30.5 V	34.1 V	–	–	141 lm/W	> 80
	6,500 K	865/469	–	3,165 lm	700 mA	32.1 V	35.9 V	–	–	134 lm/W	> 80
Operating mode NM at 900 mA											
ELA 600x600mm 3800lm 827-865 ADV2	2,700 K	827/469	3,850 lm	3,590 lm	900 mA	32.9 V	36.6 V	34.9 W	123 lm/W	116 lm/W	> 80
	3,000 K	830/469	–	3,705 lm	900 mA	32.9 V	36.6 V	–	–	119 lm/W	> 80
	4,000 K	840/469	–	3,995 lm	900 mA	31.2 V	34.8 V	–	–	135 lm/W	> 80
	6,500 K	865/469	–	3,995 lm	900 mA	32.9 V	36.6 V	–	–	129 lm/W	> 80
ELA 600x600mm 3800lm 827-865 ADV2 TPA	2,700 K	827/469	3,390 lm	3,590 lm	900 mA	32.9 V	36.6 V	31.4 W	108 lm/W	116 lm/W	> 80
	3,000 K	830/469	–	3,705 lm	900 mA	32.9 V	36.6 V	–	–	119 lm/W	> 80
	4,000 K	840/469	–	3,995 lm	900 mA	31.2 V	34.8 V	–	–	135 lm/W	> 80
	6,500 K	865/469	–	3,995 lm	900 mA	32.9 V	36.6 V	–	–	129 lm/W	> 80
Operating mode HO at 1,000 mA											
ELA 600x600mm 3800lm 827-865 ADV2	2,700 K	827/469	–	4,110 lm	1,000 mA	33.3 V	37.2 V	–	–	112 lm/W	> 80
	3,000 K	830/469	–	4,240 lm	1,000 mA	33.3 V	37.2 V	–	–	115 lm/W	> 80
	4,000 K	840/469	–	4,565 lm	1,000 mA	31.6 V	35.4 V	–	–	130 lm/W	> 80
	6,500 K	865/469	–	4,565 lm	1,000 mA	33.3 V	37.2 V	–	–	124 lm/W	> 80
ELA 600x600mm 3800lm 827-865 ADV2 TPA	2,700 K	827/469	–	4,110 lm	1,000 mA	33.3 V	37.2 V	–	–	112 lm/W	> 80
	3,000 K	830/469	–	4,240 lm	1,000 mA	33.3 V	37.2 V	–	–	115 lm/W	> 80
	4,000 K	840/469	–	4,565 lm	1,000 mA	31.6 V	35.4 V	–	–	130 lm/W	> 80
	6,500 K	865/469	–	4,565 lm	1,000 mA	33.3 V	37.2 V	–	–	124 lm/W	> 80

[®] Integral measurement over the complete module.

[®] Measured at Imax.

[®] HE ... High Efficiency, NM ... Nominal Mode, HO ... High Output.


[®] Tolerance of useful light flux - 0 % / + 15 %. Measurement uncertainty ± 10 %.

[®] Tolerance of expected light flux - 0 % / + 15 %. Measurement uncertainty ± 10 %. Based on calculation.

[®] Tolerance of power consumption Pon ± 10 %. Measurement uncertainty ± 5 %.

Product description


- Aluminum frame for easy surface mounting



ACE Surface mount kit 600mm AL WH G2



ACE Surface mount kit 600mm AL WH G2 assembled




ACE Surface mount kit 600mm AL WH G2

Ordering data


Type	Article number	Colour	Packaging	Weight per pc.
ACE Surface mount kit 600mm AL WH G2	28003372	White	20 pc(s).	0.483 kg

Product description

- Steel wire system for suspended mounting
- Suspension height up to 1.2 m



ACE Suspension kit 600-625mm STL SI G2




ACE Suspension kit 600-625mm STL SI G

Ordering data

Type	Article number	Colour	Packaging	Weight per pc.
ACE Suspension kit 600-625mm STL SI G2	28003374	Silver	100 pc(s).	0.097 kg

Product description

- Additional 3way CCT-SWITCH connector for easy CCT change among 3,000 K / 4,000 K / 6,500 K
- Enables the colour temperature to be changed without replacing the ELA module
- Switching during operation is not permitted. The LED driver must be switched off before switching.
- Length 400 mm
- Wire cross section AWG 22



Ordering data

Type	Article number	Colour	Packaging	Weight per pc.
ACE 3way CCT-SWITCH 400mm WH	28003294	White	50 pc(s).	0.029 kg

1. Standards

EN 62031
EN 62471
EN 61000-4-2
EN 62717
EN 60598-1

1.1 Photometric code

Key for photometric code, e. g. 830 / 359

1 st digit	2 nd + 3 rd digit	4 th digit	5 th digit	6 th digit
Code CRI	Colour temperature in Kelvin x 100	MacAdam initial	MacAdam after 25% of the lifetime (max.6000h)	Luminous flux after 25% of the lifetime (max.6000h)
7 70 – 79				Code Luminous flux
8 80 – 89				7 ≥ 70 %
9 ≥90				8 ≥ 80 %
				9 ≥ 90 %

1.2 Energy classification

Type	Colour temperature	Forward current	Energy classification	Energy consumption
ELA 600x600mm 3800lm 827-865 ADV2	2,700 K	900 mA	E	32 kWh / 1,000 h
ELA 600x600mm 3800lm 827-865 ADV2 TPA	2,700 K	900 mA	E	32 kWh / 1,000 h

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

2. Thermal details

2.1 tc point, ambient temperature and lifetime


The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For ELA a tp temperature of 45 °C has to be complied in order to achieve an optimum between light output and lifetime.

Compliance with the maximum permissible reference temperature at the tc point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

ELA 600x600 3800lm 827-865 ADV2:



2.2 Storage and humidity

Storage temperature	-20 ... +50 °C
---------------------	----------------

Operation only in non condensing environment.

Humidity during operation of the module should be between 0 to 70 %.

2.3 Thermal design and heat sink

The rated life of LED products depends to a large extent on the operating temperature.

If the permissible temperature limits are exceeded, the life of the ELA will be greatly reduced or the ELA may be destroyed.

3. Installation / wiring

3.1 Electrical supply/choice of LED driver

ELA modules from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED driver from Tridonic in combination with ELA modules guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



ELA modules must be supplied by a constant current LED driver. Operation with a constant voltage LED driver will lead to an irreversible damage of the module.


Wrong polarity can damage the ELA.



ELA modules must be operated with SELV LED drivers. ELA modules are not designed for parallel or serial wiring. A separate driver or output channel (for multi-channel LED drivers) must be used for each ELA module.


3.2 Wiring

Wiring diagram with CCT-SWITCH




LED driver	Article number
LC 30/700/43 fixC SR SNC2	87500757
LC 30/700/42 fixC SC ADV2	87500892
LC 40/900/45 fixC SR SNC2	87500762
LC 38/900/42 fixC SC ADV2	87500894


Wiring diagram switchDIM and colourSWITCH with DALI Driver (28002202 – LCA 38W 350-1050mA DT8 SR PRE)



Wiring diagram DALI with DALI Driver (28002202 – LCA 38W 350-1050mA DT8 SR PRE)



3.3 Wiring type and cross section



ELA has a pre-installed, flexible connection cable for easy connection of the driver during installation
Wire cross section: AWG22
Stripping length: 9 mm, pre-tinned

3.4 Mounting instruction



None of the components of the ELA (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.

Recessed mounting for suspended ceilings with grid measure of 600 or 625 mm.

For surface mounted applications use the ACE Surface mount kit and for suspended mounting the ACE Suspension kit.
For more details see mounting instructions.

To prevent fingerprints we recommend to mount the ELA only with gloves.



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

3.5 EOS/ESD safety guidelines



The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice. Please note the requirements set out in the document EOS / ESD guidelines (Guideline_EOS_ESD.pdf) at: <http://www.tridonic.com/esd-protection>

4. Lifetime

4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value.

L70 means that the LED module will give 70 % of its initial luminous flux. This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

The L value is a statistical value and the lumen maintenance may vary over the delivered LED modules.

The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value. In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance for ELA

Forward current	tp temperature	L90 / B10	L90 / B50	L80 / B10	L80 / B50	L70 / B10	L70 / B50
700 /	45 °C	28k h	32k h	>50k h	>50k h	>50k h	>50k h
	55 °C	28k h	32k h	>50k h	>50k h	>50k h	>50k h
900 /	65 °C	25k h	28k h	>50k h	>50k h	>50k h	>50k h
	70 °C	22k h	25k h	>50k h	>50k h	>50k h	>50k h

Lumen maintenance values are based on LM80 data. Table may be updated when more recent results are available.

4.3 Switching capability

25,000 cycles

Test according to IEC 62717 CI 10.3.3
30 s on / 30 s off at Imax

5. Electrical values

5.1 Declaration of electrical parameters


I_{rated} ... Nominal operating current the module is designed for.

I_{max} ... Max. permissible continuous operating current incl. the tolerances of the LED driver.


Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.

Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

5.2 Typ. forward voltage vs. forward current



5.3 Forward voltage vs. T_c temperature



The diagrams are based on statistic values.

The real values can be different.

6. Photometric characteristics

6.1 Coordinates and tolerances according to CIE 1931


The specified colour coordinates are measured integral by a current impulse at the rated current. Integration time is 100 ms.

The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$.


The measurement tolerance of the colour coordinates are ± 0.005 .

2,700 K

	x0	y0
Centre	0.4622	0.4148




MacAdam Ellipse: 4SDCM




3,000 K

	x0	y0
Centre	0.4412	0.4040




MacAdam Ellipse: 4SDCM




4,000 K

	x0	y0
Centre	0.3760	0.3707




MacAdam Ellipse: 4SDCM




6,500 K

	x0	y0
Centre	0.3128	0.3390




— MacAdam Ellipse: 4SDCM




6.2 Light distribution

The optical design of the ELA product line ensures optimum homogeneity for the light distribution.

ELA 600x600 3800lm 827-865 ADV2:




ELA 600x600 3800lm 827-865 ADV2 TPA:




The colour temperature is measured integral over the complete module. The single LED light points can have deviations in the colour coordinates.

The random appearance of minor shining dots is state of the art and technologically inevitable. This does not qualify for returns or warranty claims.

6.3 Relative luminous flux vs. tc temperature



6.4 Relative luminous flux vs. operating current



7. Miscellaneous

7.1 Additional information

Additional technical information at www.tridonic.com → Technical Data

Guarantee conditions at www.tridonic.com → Services

Lifetime declarations are informative and represent no warranty claim.