



Module LLE 24mm 1250lm CRI90 LV ADV5

Modules LLE advanced

Product description

- Ideal for linear and panel lights
- 4 terminals for parallel wiring
- 4,000 K module COI approved acc. to AS/NZS1680.2.5:1997
- Perfectly uniform light, even if several LED modules are used together in a line
- Push terminals for quick and simple wiring of LED module to LED module
- Broad portfolio from extruded lenses and covers available
- Long lifetime: 72,000 hours
- 5 years guarantee (conditions at www.tridonic.com)

Optical properties

- Colour temperatures 2,700 K, 3,000 K, 3,500 K and 4,000 K
- Useful luminous flux 2,118 lm at Irated and tp = 25 °C
- Efficacy of the LED module 160 lm/W at Irated and tp = 25 °C
- High colour rendering index CRI > 90
- High colour consistency (MacAdam 3)[®]
- Small luminous flux tolerances

Mechanical properties

- Module dimension 24 x 140 mm, 24 x 280 mm and 24 x 560 mm (ZHAGA compliant)
- Simple installation (e.g. clips or screws)


System solution

- Combine Tridonic`s LED modules and dimmable drivers to achieve an outstanding system efficacy (configuration possible via <https://setbuilder.tridonic.com/>)



Standards, page 10

Colour temperatures and tolerances, page 14




LLE 24x140mm 650lm LV ADV5



LLE 24x280mm 1250lm LV ADV5



LLE 24x560mm 2400lm LV ADV5






Module LLE 24mm 1250lm CRI90 LV ADV5


Modules LLE advanced

Technical data


Beam characteristic	120°
Ambient temperature range	-40 ... +65 °C
tp rated	50 °C
tc	85 °C
Irated for 650 lm	100 mA
Irated for 1,250 lm	200 mA
Irated for 2,400 lm	400 mA
Imax for 650 lm	180 mA
Imax for 1,250 lm	360 mA
Imax for 2,400 lm	720 mA
Max. permissible LF current ripple for 650 lm	200 mA
Max. permissible LF current ripple for 1,250 lm	400 mA
Max. permissible LF current ripple for 2,400 lm	800 mA
Max. permissible peak current for 650 lm	300 mA / max. 10 ms
Max. permissible peak current for 1,250 lm	600 mA / max. 10 ms
Max. permissible peak current for 2,400 lm	1,200 mA / max. 10 ms
Max. working voltage for insulation SELV®	60 V
Insulation test voltage	0.5 kV
CTI of the printed circuit board	≥ 600
ESD classification	severity level 4
Risk group (IEC 62471)	RG0
Classification acc. to IEC 62031	Built-in
Type of protection	IP00
Lumen maintenance L70B50	72,000 h
Guarantee	5 years



LLE 24x140mm 650lm LV ADV5



LLE 24x280mm 1250lm LV ADV5



LLE 24x560mm 2400lm LV ADV5

Ordering data

Type	Article number	Colour temperature	Packaging carton	Weight per pc.
LLE 24x140mm 650lm 930 LV ADV5	89603345	3,000 K	420 pc(s).	0.011 kg
LLE 24x140mm 650lm 935 LV ADV5	28003414	3,500 K	420 pc(s).	0.011 kg
LLE 24x140mm 650lm 940 LV ADV5	89603346	4,000 K	420 pc(s).	0.011 kg
LLE 24x280mm 1250lm 927 LV ADV5	89603347	2,700 K	210 pc(s).	0.023 kg
LLE 24x280mm 1250lm 930 LV ADV5	89603348	3,000 K	210 pc(s).	0.023 kg
LLE 24x280mm 1250lm 935 LV ADV5	28003415	3,500 K	210 pc(s).	0.023 kg
LLE 24x280mm 1250lm 940 LV ADV5	89603349	4,000 K	210 pc(s).	0.023 kg
LLE 24x560mm 2400lm 930 LV ADV5	89603351	3,000 K	180 pc(s).	0.046 kg
LLE 24x560mm 2400lm 935 LV ADV5	28003416	3,500 K	180 pc(s).	0.046 kg
LLE 24x560mm 2400lm 940 LV ADV5	89603352	4,000 K	180 pc(s).	0.046 kg

Specific technical data

Type [®]	Photo-metric code	Useful luminous flux at tp = 25 °C ^④	Expected luminous flux at tp rated ^⑤	Typ. forward current	Min. forward voltage at tp rated	Max. forward voltage at tp = 25 °C	Power consumption Pon at tp = 25 °C ^⑥	Efficacy of the module at tp = 25 °C	Expected efficacy of the module at tp rated	Colour rendering index CRI
Operating mode HE at 150 mA per foot (280 mm module length)										
LLE 24x140mm 650lm 930 LV ADV5	930/359	–	385 lm	75 mA	31.2 V	33.8 V	–	–	159 lm/W	> 90
LLE 24x140mm 650lm 935 LV ADV5	935/359	–	395 lm	75 mA	31.2 V	33.8 V	–	–	163 lm/W	> 90
LLE 24x140mm 650lm 940 LV ADV5	940/359	–	398 lm	75 mA	31.2 V	33.8 V	–	–	165 lm/W	> 90
LLE 24x280mm 1250lm 927 LV ADV5	927/359	–	744 lm	150 mA	31.2 V	33.8 V	–	–	150 lm/W	> 90
LLE 24x280mm 1250lm 930 LV ADV5	930/359	–	765 lm	150 mA	31.2 V	33.8 V	–	–	156 lm/W	> 90
LLE 24x280mm 1250lm 935 LV ADV5	935/359	–	789 lm	150 mA	31.2 V	33.8 V	–	–	161 lm/W	> 90
LLE 24x280mm 1250lm 940 LV ADV5	940/359	–	797 lm	150 mA	31.2 V	33.8 V	–	–	163 lm/W	> 90
LLE 24x560mm 2400lm 930 LV ADV5	930/359	–	1,532 lm	300 mA	31.2 V	33.8 V	–	–	157 lm/W	> 90
LLE 24x560mm 2400lm 935 LV ADV5	935/359	–	1,589 lm	300 mA	31.2 V	33.8 V	–	–	162 lm/W	> 90
LLE 24x560mm 2400lm 940 LV ADV5	940/359	–	1,601 lm	300 mA	31.2 V	33.8 V	–	–	164 lm/W	> 90
Operating mode NM at 200 mA per foot (280 mm module length)										
LLE 24x140mm 650lm 930 LV ADV5	930/359	507 lm	492 lm	100 mA	31.6 V	34.2 V	3.3 W	154 lm/W	151 lm/W	> 90
LLE 24x140mm 650lm 935 LV ADV5	935/359	525 lm	510 lm	100 mA	31.6 V	34.2 V	3.3 W	159 lm/W	155 lm/W	> 90
LLE 24x140mm 650lm 940 LV ADV5	940/359	529 lm	514 lm	100 mA	31.6 V	34.2 V	3.3 W	160 lm/W	157 lm/W	> 90
LLE 24x280mm 1250lm 927 LV ADV5	927/359	979 lm	959 lm	200 mA	31.6 V	34.2 V	6.7 W	146 lm/W	143 lm/W	> 90
LLE 24x280mm 1250lm 930 LV ADV5	930/359	1,014 lm	985 lm	200 mA	31.6 V	34.2 V	6.7 W	151 lm/W	148 lm/W	> 90
LLE 24x280mm 1250lm 935 LV ADV5	935/359	1,049 lm	1,019 lm	200 mA	31.6 V	34.2 V	6.7 W	157 lm/W	153 lm/W	> 90
LLE 24x280mm 1250lm 940 LV ADV5	940/359	1,059 lm	1,030 lm	200 mA	31.6 V	34.2 V	6.7 W	158 lm/W	155 lm/W	> 90
LLE 24x560mm 2400lm 930 LV ADV5	930/359	2,029 lm	1,970 lm	400 mA	31.6 V	34.2 V	13.2 W	153 lm/W	150 lm/W	> 90
LLE 24x560mm 2400lm 935 LV ADV5	935/359	2,099 lm	2,039 lm	400 mA	31.6 V	34.2 V	13.2 W	158 lm/W	154 lm/W	> 90
LLE 24x560mm 2400lm 940 LV ADV5	940/359	2,118 lm	2,059 lm	400 mA	31.6 V	34.2 V	13.2 W	159 lm/W	156 lm/W	> 90
Operating mode HO at 330 mA per foot (280 mm module length)										
LLE 24x140mm 650lm 930 LV ADV5	930/359	–	790 lm	165 mA	32.7 V	35.3 V	–	–	142 lm/W	> 90
LLE 24x140mm 650lm 935 LV ADV5	935/359	–	815 lm	165 mA	32.7 V	35.3 V	–	–	146 lm/W	> 90
LLE 24x140mm 650lm 940 LV ADV5	940/359	–	820 lm	165 mA	32.7 V	35.3 V	–	–	148 lm/W	> 90
LLE 24x280mm 1250lm 927 LV ADV5	927/359	–	1,527 lm	330 mA	32.7 V	35.3 V	–	–	135 lm/W	> 90
LLE 24x280mm 1250lm 930 LV ADV5	930/359	–	1,580 lm	330 mA	32.7 V	35.3 V	–	–	140 lm/W	> 90
LLE 24x280mm 1250lm 935 LV ADV5	935/359	–	1,628 lm	330 mA	32.7 V	35.3 V	–	–	144 lm/W	> 90
LLE 24x280mm 1250lm 940 LV ADV5	940/359	–	1,642 lm	330 mA	32.7 V	35.3 V	–	–	145 lm/W	> 90
LLE 24x560mm 2400lm 930 LV ADV5	930/359	–	3,161 lm	660 mA	32.7 V	35.3 V	–	–	141 lm/W	> 90
LLE 24x560mm 2400lm 935 LV ADV5	935/359	–	3,268 lm	660 mA	32.7 V	35.3 V	–	–	145 lm/W	> 90
LLE 24x560mm 2400lm 940 LV ADV5	940/359	–	3,299 lm	660 mA	32.7 V	35.3 V	–	–	147 lm/W	> 90

^① Integral measurement over the complete module.

^② If mounted with M4 screws and plastic washers.

^③ HE ... high efficiency, NM ... nominal mode, HO ... high output.


^④ Tolerance of useful light flux - 0 % / + 15 %. Measurement uncertainty ± 10 %.

^⑤ Tolerance of expected light flux - 0 % / + 15 %. Measurement uncertainty ± 10 %. Based on calculation.

^⑥ Tolerance of power consumption Pon ± 10 %. Measurement uncertainty ± 5 %.

Product description

- LINEAR COVER for LLE 24
- Protection against direct touch for non-SELV applications
(recommendation: use all fixing points)
- Fast snap on mounting on to LLE 24 with clips or plastic washers
- High transmission: transparent 94 %, semi-transparent 87 %, diffuse 76 %
- Made of PMMA
- Tolerances: ± 1 mm for 597 mm length (ends finished),
+ 10 mm for 1,200 / 1,500 / 1,600 / 1,800 mm length (ends raw)



Ordering data

Type	Article number	Colour	Length	Packaging carton	Weight per pc.
LINEAR COVER SY Transparent 1600mm	28000338	Transparent	1,600 mm	12 pc(s).	0.272 kg
LINEAR COVER SY Frosted 1800mm	28000437	Semi-transparent	1,800 mm	12 pc(s).	0.308 kg
LINEAR COVER SY Frosted 1600mm	28000339	Semi-transparent	1,600 mm	12 pc(s).	0.272 kg
LINEAR COVER SY Frosted 1500mm	28000435	Semi-transparent	1,500 mm	12 pc(s).	0.244 kg
LINEAR COVER SY Frosted 1200mm	28000422	Semi-transparent	1,200 mm	12 pc(s).	0.205 kg
LINEAR COVER SY Frosted 597mm	28000340	Semi-transparent	597 mm	12 pc(s).	0.102 kg
LINEAR COVER SY Diffuse 1800mm	28000438	Diffuse	1,800 mm	12 pc(s).	0.308 kg
LINEAR COVER SY Diffuse 1600mm	28000341	Diffuse	1,600 mm	12 pc(s).	0.272 kg
LINEAR COVER SY Diffuse 1500mm	28000436	Diffuse	1,500 mm	12 pc(s).	0.257 kg
LINEAR COVER SY Diffuse 1200mm	28000434	Diffuse	1,200 mm	12 pc(s).	0.205 kg
LINEAR COVER SY Diffuse 597mm	28000342	Diffuse	597 mm	12 pc(s).	0.102 kg

Product description


- ENDCAP for LLE 24
- PUSH-FIX: Fast snap on mounting (sheet thickness 0.5 – 1.0 mm), for drilling hole 4 mm
- SCREW-FIX: Screw mounting with EJOT Delta PT WN 5451 30x8 (not included), tightening torque 0.7 Nm
- Made of Polycarbonat




ACL ENDCAP LLE24 PUSH-FIX



ACL ENDCAP LLE24 SCREW-FIX



ACL ENDCAP LLE24 PUSH-FIX



ACL ENDCAP LLE24 SCREW-FIX

Ordering data

Type	Article number	Colour	Packaging carton	Weight per pc.
ACL ENDCAP LLE24 PUSH-FIX	28001037	White	480 pc(s).	0.003 kg
ACL ENDCAP LLE24 SCREW-FIX	28002315	White	480 pc(s).	0.003 kg

Product description LINEAR LENS

- Linear lens for LLE 24
- Available with different beam characteristics
- Protection against direct touch for non-SELV applications (recommendation: use all fixing points)
- Fast snap on mounting on to LLE 24 with clips or plastic washers
- Linear lense made of PMMA
- Available lengths: 1,200, 1,500, 1,600 and 1,800 mm, Tolerance: + 10 mm (ends raw)
- Max. permissible temperature 80 °C
- Photometric data available on website

Product description Endcap

- ENDCAP for LINEAR LENS 24mm INTENSE, ASY and DASY
- Mounting by clipping in and screwing from below using screw EJOT Delta PT WN 5451 20x4, tightening torque 0.7 Nm
- Made of Polyamide UL94 V0



ACL LINEAR LENS 24mm 60°



ACL LINEAR LENS 24mm 90°



ACL LINEAR LENS 24mm INTENSE



ACL LINEAR LENS 24mm BATWING



ACL LINEAR LENS 24mm ASY




ACL LINEAR LENS 24mm DASY




ACL Endcap LENS 24mm PSF


ACL LENS 24mm




ACL LINEAR LENS 24mm 60° and 90°




ACL LINEAR LENS 24mm INTENSE



ACL LINEAR LENS 24mm BATWING




ACL LINEAR LENS 24mm ASY



ACL LINEAR LENS 24mm DASY

ACL LENS 24mm



ACL Endcap LENS 24mm PSF

Ordering data

Type	Article number	Beam characteristic	Efficiency	Packaging carton	Weight per pc.
ACL LINEAR LENS 24x1200mm 60°	28001428	60°	97 %	21 pc(s).	0.196 kg
ACL LINEAR LENS 24x1200mm 90°	28001429	90°	97 %	21 pc(s).	0.165 kg
ACL LINEAR LENS 24x1500mm 60°	28000953	60°	97 %	21 pc(s).	0.261 kg
ACL LINEAR LENS 24x1500mm 90°	28000955	90°	97 %	21 pc(s).	0.221 kg
ACL LINEAR LENS 24x1200mm INTENSE	28002024	40°	95 %	18 pc(s).	0.261 kg
ACL LINEAR LENS 24x1500mm INTENSE	28002025	40°	95 %	18 pc(s).	0.326 kg
ACL LINEAR LENS 24x1800mm INTENSE	28002026	40°	95 %	18 pc(s).	0.392 kg
ACL LINEAR LENS 24x1200mm BATWING	28002027	batwing	95 %	18 pc(s).	0.275 kg
ACL LINEAR LENS 24x1500mm BATWING	28002028	batwing	95 %	18 pc(s).	0.344 kg
ACL LINEAR LENS 24x1800mm BATWING	28002029	batwing	95 %	18 pc(s).	0.412 kg
ACL LINEAR LENS 24x1200mm ASY	28002030	asymmetric	95 %	18 pc(s).	0.250 kg
ACL LINEAR LENS 24x1500mm ASY	28002031	asymmetric	95 %	18 pc(s).	0.312 kg
ACL LINEAR LENS 24x1800mm ASY	28002032	asymmetric	95 %	18 pc(s).	0.375 kg
ACL LINEAR LENS 24x1200mm DASY	28002033	double asymmetric	92 %	18 pc(s).	0.249 kg
ACL LINEAR LENS 24x1500mm DASY	28002034	double asymmetric	92 %	18 pc(s).	0.311 kg
ACL LINEAR LENS 24x1800mm DASY	28002035	double asymmetric	92 %	18 pc(s).	0.373 kg
ACL Endcap LENS 24mm PSF	28002669	–	–	3,600 pc(s).	0.003 kg

**ACCES-
SORIES**


CLIP 4.3mm

Product description

- Clip for fixation of LED modules with 4.3 mm holes
- Fast snap on mounting (sheet thickness 0.5 – 1.0 mm for PUSH-FIX and 1 – 2 mm for PUSH-FIX Long)
- For drilling hole 4 mm
- Clip made of Polycarbonat




ACL CLIP 4.3mm PUSH-FIX



ACL CLIP 4.3mm PUSH-FIX



ACL CLIP 4.3mm PUSH-FIX Long



ACL CLIP 4.3mm PUSH-FIX Long

Ordering data

Type	Article number	Colour	Packaging bag ^①	Weight per pc.
ACL CLIP 4.3mm PUSH-FIX	28001036	White	500 pc(s).	0.001 kg
ACL CLIP 4.3mm PUSH-FIX Long	28002314	Transparent	500 pc(s).	0.001 kg


^① Minimum sales quantity 500 pcs.

**ACCES-
SORIES**

BRIDGE LLE24/40

Product description

- Enables the fixation of 24 mm wide Tridonic LED modules to fixtures made for 40 mm wide modules
- Ideal for extruded aluminium gear trays made for 40 mm modules with pre-alignment knobs
- Clip-on for LINEAR COVER and LINEAR LENS[®]
- For LLE 24 with 280 mm module minimum 2 bridges required
- For LLE 24 with 560 mm module minimum 3 bridges required
- Fixation via M3 or M4 countersunk screw, max. tightening torque 0.5 Nm
- BRIDGE made of white polycarbonate



Ordering data

Type	Article number	Colour	Packaging carton ^①	Weight per pc.
ACL BRIDGE LLE24/40 SCREW-FIX	28001205	White	600 Stk.	0.001 kg

^① Minimum sales quantity 600 pcs.

^② Beam characteristics will change due to the elevated fixation (see photometric files for details).

1. Standards

IEC 62031
IEC 62471
IEC 61000-4-2
IEC 62778
IEC 61547
UL 8750 (for CLASS2 circuits and dry locations)

1.1 Photometric code

Key for photometric code, e. g. 830 / 349

1 st digit	2 nd + 3 rd digit	4 th digit	5 th digit	6 th digit
Code	CRI	Colour temperature in Kelvin x 100	MacAdam initial	MacAdam after 25% of the lifetime (max.6000h)
7	70 – 79	Kelvin x 100	MacAdam initial	Luminous flux after 25% of the lifetime (max.6000h)
8	80 – 89			Code
9	≥90			7
				8
				9

1.2 Energy classification

Type	Colour temperature	Forward current	Energy classification	Energy consumption
LLE 24x140mm 650lm 930 LV ADV5	3,000 K	75 mA	D	4 kWh / 1,000 h
LLE 24x140mm 650lm 935 LV ADV5	3,500 K	75 mA	D	4 kWh / 1,000 h
LLE 24x140mm 650lm 940 LV ADV5	4,000 K	75 mA	D	4 kWh / 1,000 h
LLE 24x280mm 1250lm 927 LV ADV5	2,700 K	150 mA	D	7 kWh / 1,000 h
LLE 24x280mm 1250lm 930 LV ADV5	3,000 K	150 mA	D	7 kWh / 1,000 h
LLE 24x280mm 1250lm 935 LV ADV5	3,500 K	150 mA	D	7 kWh / 1,000 h
LLE 24x280mm 1250lm 940 LV ADV5	4,000 K	150 mA	D	7 kWh / 1,000 h
LLE 24x560mm 2400lm 930 LV ADV5	3,000 K	300 mA	D	14 kWh / 1,000 h
LLE 24x560mm 2400lm 935 LV ADV5	3,500 K	300 mA	D	14 kWh / 1,000 h
LLE 24x560mm 2400lm 940 LV ADV5	4,000 K	300 mA	D	14 kWh / 1,000 h

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

2. Thermal details

2.1 tc point, ambient temperature and lifetime

The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For LLE a tp temperature of 50 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and lifetime.

Compliance with the maximum permissible reference temperature at the tc point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

2.2 Storage and humidity

Storage temperature	-40 ... +80 °C
---------------------	----------------

Operation only in non condensing environment.

Humidity during processing of the module should be between 30 to 70 %.

2.3 Heat sink values

LLE 24x140mm 650lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	100 mA	14.72 K/W	45 cm ²
25 °C	50 °C	165 mA	8.02 K/W	83 cm ²
35 °C	50 °C	100 mA	8.83 K/W	76 cm ²
35 °C	50 °C	165 mA	4.81 K/W	139 cm ²
40 °C	50 °C	100 mA	5.88 K/W	113 cm ²
40 °C	50 °C	165 mA	3.20 K/W	208 cm ²
45 °C	50 °C	100 mA	2.93 K/W	227 cm ²
45 °C	50 °C	165 mA	1.59 K/W	418 cm ²

LLE 24x280mm 1250lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	200 mA	7.31 K/W	91 cm ²
25 °C	50 °C	330 mA	4.01 K/W	166 cm ²
35 °C	50 °C	200 mA	4.38 K/W	152 cm ²
35 °C	50 °C	330 mA	2.40 K/W	277 cm ²
40 °C	50 °C	200 mA	2.92 K/W	228 cm ²
40 °C	50 °C	330 mA	1.60 K/W	416 cm ²
45 °C	50 °C	200 mA	1.46 K/W	458 cm ²
45 °C	50 °C	330 mA	0.80 K/W	836 cm ²

LLE 24x560mm 2400lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	400 mA	3.66 K/W	182 cm ²
25 °C	50 °C	660 mA	2.01 K/W	332 cm ²
35 °C	50 °C	400 mA	2.19 K/W	258 cm ²
35 °C	50 °C	660 mA	1.20 K/W	555 cm ²
40 °C	50 °C	400 mA	1.46 K/W	457 cm ²
40 °C	50 °C	660 mA	0.80 K/W	833 cm ²
45 °C	50 °C	400 mA	0.73 K/W	915 cm ²
45 °C	50 °C	660 mA	0.40 K/W	1,673 cm ²

Notes

The actual cooling surface can differ because of the material, the structural shape, outside influences and the installation situation. Depending on the heat sink a heat conducting paste or heat conducting film might be necessary to keep the specified tp temperature.

3. Installation / wiring

3.1 Electrical supply/choice of LED driver

LLE modules from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED driver from Tridonic in combination with LLE modules guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



LLE modules must be supplied by a constant current LED driver. Operation with a constant voltage LED driver will lead to an irreversible damage of the module.

Wrong polarity can damage the LLE.

With parallel wiring tolerance-related differences in output are possible (thermal stress of the module) and can cause differences in brightness. For best homogeneity, only connect modules from one batch in parallel.

If a wire breaks or a complete module fails then the current passing through the other module increases. This may reduce its life considerably.


The max. permissible output current of the LED driver for parallel wiring is 3 A.

LLE have to be operated with SELV LED drivers.







LLE are basic insulated up to 60 V SELV (if mounted with M4 screws with head diameter 7 mm in combination with plastic washers) against ground and can be mounted directly on earthed metal parts of the luminaire. If the max. output voltage of the LED driver (also against earth) is above 60 V SELV, an additional insulation between LED module and heat sink is required (for example by insulated thermal pads) or by a suitable luminaire construction.

3.2 Wiring



Wiring examples




Type	Recommendation for max. number with parallel wiring*
LLE 24x140mm 650lm LV ADV5	12
LLE 24x280mm 1250lm LV ADV5	6
LLE 24x560mm 2400lm LV ADV5	3

* with direkt chaining (without additional terminals).

3.3 Wiring type and cross section

For wiring use stranded wire with ferrules or solid wire from 0.2 to 0.75 mm². For the push-wire connection you have to strip the insulation (8–9 mm).



To remove the wires use a suitable tool (e.g. Microcon release pin) or through twist and pull.

3.4 Mounting instruction



None of the components of the LLE (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.

Max. torque for fixing: 0.5 Nm.

The LED modules are mounted onto a heat sink with min. 3 screws per module or ACL CLIP 4.3mm.



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

3.5 EOS/ESD safety guidelines



The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice. Please note the requirements set out in the document EOS / ESD guidelines (Guideline_EOS_ESD.pdf) at: <http://www.tridonic.com/esd-protection>

4. Lifetime

4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value.
L70 means that the LED module will give 70 % of its initial luminous flux.
This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules.

The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value.
In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance for LLE 24mm LV ADV5

Forward current	tp tempera- ture	L90 / F10	L90 / F50	L80 / F10	L80 / F50	L70 / F10	L70 / F50
100 mA / ft (280 mm module length)	40 °C	43,000 h	59,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	45 °C	42,000 h	57,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	50 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	60 °C	39,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	65 °C	38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	70 °C	38,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	75 °C	37,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	80 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	85 °C	35,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
130 mA / ft (280 mm module length)	40 °C	43,000 h	58,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	45 °C	42,000 h	57,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	50 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	40,000 h	53,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	60 °C	39,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	65 °C	38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	70 °C	37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	75 °C	36,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	80 °C	36,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	85 °C	35,000 h	44,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
200 mA / ft (280 mm module length)	40 °C	42,000 h	58,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	45 °C	41,000 h	56,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	50 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	40,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	60 °C	39,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	65 °C	38,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	70 °C	37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	75 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	80 °C	35,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	85 °C	34,000 h	44,000 h	70,000 h	>72,000 h	>72,000 h	>72,000 h
250 mA / ft (280 mm module length)	40 °C	42,000 h	57,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	45 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	50 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	39,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	60 °C	38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	65 °C	37,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	70 °C	37,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	75 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	80 °C	35,000 h	44,000 h	71,000 h	>72,000 h	>72,000 h	>72,000 h
	85 °C	34,000 h	43,000 h	69,000 h	>72,000 h	>72,000 h	>72,000 h
300 mA / ft (280 mm module length)	40 °C	42,000 h	56,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	45 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	50 °C	40,000 h	53,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	39,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	60 °C	38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	65 °C	37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	70 °C	36,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	75 °C	35,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	80 °C	35,000 h	44,000 h	70,000 h	>72,000 h	>72,000 h	>72,000 h
	85 °C	34,000 h	43,000 h	69,000 h	>72,000 h	>72,000 h	>72,000 h
330 mA / ft (280 mm module length)	40 °C	41,000 h	56,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	45 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	50 °C	39,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	38,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	60 °C	38,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	65 °C	37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	70 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	75 °C	35,000 h	45,000 h	71,000 h	>72,000 h	>72,000 h	>72,000 h
	80 °C	34,000 h	43,000 h	70,000 h	>72,000 h	>72,000 h	>72,000 h
	85 °C	34,000 h	42,000 h	68,000 h	>72,000 h	>72,000 h	>72,000 h

4.3 Switching capability

100,000 cycles

Tridonic test according to IEC 62717 Cl 10.3.3
30 s on / 30 s off at Imax

5. Electrical values

5.1 Declaration of electrical parameters

Irated ... Nominal operating current the module is designed for.


I_{max} ... Max. permissible continuous operating current incl. The tolerances of the LED driver.

Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.


Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

5.2 Typ. forward voltage vs. forward current


LLE 24x140mm 650lm 9xx LV ADV5




LLE 24x280mm 1250lm 9xx LV ADV5



LLE 24x560mm 2400lm 9xx LV ADV5



5.3 Forward voltage vs. tc temperature



The diagrams are based on statistic values.
The real values can be different.


6. Photometric characteristics

6.1 Coordinates and tolerances according to CIE 1931


The specified colour coordinates are integral measured by current impulse of 195 mA and a duration of 100 ms.
The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$.
The measurement tolerance of the colour coordinates are ± 0.01 .

2,700 K



	x0	y0
Centre	0.4578	0.4101



TM30		CRI	
Rf	Rg	Ra	R9
91	99	93	57




Colour vector graphic




3,000 K

	x0	y0
Centre	0.4338	0.4030




— MacAdam Ellipse: 3SDCM


TM30		CRI	
Rf	Rg	Ra	R9
90	98	92	57



Colour vector graphic




— Reference source
— Test source






3,500 K

	x0	y0
Centre	0.4073	0.3917




TM30		CRI	
Rf	Rg	Ra	R9
90	99	93	63

Colour vector graphic




4,000 K

	x0	y0
Center	0.3818	0.3797




— MacAdam Ellipse: 3SDCM


TM30		CRI	
Rf	Rg	Ra	R9
89	99	91	54



Colour vector graphic




— Reference source
— Test source



6.2 Light distribution


The optical design of the LLE product line ensures optimum homogeneity for the light distribution.



The colour temperature is measured integral over the complete module. The single LED light points can have deviations in the colour coordinates within MacAdam 3.


To ensure an ideal mixture of colours and a homogeneous light distribution a suitable optic (e. g. PMMA diffuser) and a sufficient spacing between module and optic (typ. 4 cm) should be used.

6.3 Relative luminous flux vs. tc temperature




6.4 Relative luminous flux vs. operating current


LLE 24x140mm 650lm 9xx LV ADV5



LLE 24x280mm 1250lm 9xx LV ADV5



LLE 24x560mm 2400lm 9xx LV ADV5



The diagrams are based on statistic values.
The real values can be different.

7. Miscellaneous

7.1 Additional information

Additional technical information at www.tridonic.com → Technical Data

Guarantee conditions at www.tridonic.com → Services

Lifetime declarations are informative and represent no warranty claim.